



## XP-370B/370BM

### Thermal Barcode Printer

- Compact and space saving design
- Easy paper load with adjustable paper guide
- Printing speed up to 152mm per second
- Max 100mm label diameter, external amount and board option
- Thermal sensitive resistance, photoelectric sensor black mark sensor
- USB+Serial+ethernet or USB+Serial or USB+Bluetooth option

### APPLICATIONS



Shopping



Mart



Hospital



Coffee Shop



Restaurant



Ticketing




Express



Factory

# XP-370B/370BM

## Desktop Barcode Printer



MODEL	XP-370B	XP-370BM	
Printing method	Direct thermal		
Resolution	203dpi (8dots/mm)		
Paper width	16~82mm		
Paper roll diameter	25mm ( Min ) for internal, 100mm ( Max ) for external		
Printing length (Max.)	1000mm		
Paper thickness	0.06~0.19mm		
Printing speed	Min: 50.8mm/s Max: 152mm/s		
Print head temperature sensor	Thermal sensitive resistance		
Bar Codes	CODE128、EAN128、ITF、CODE39、CODE93、EAN13、EAN13+2、EAN13+5、EAN8、EAN8+2、EAN8+5、CODABAR、POSTNET、UPC-A、UPCA+2、UPCA+5、UPC-E、UPCE+2、UPC-E+5、CPOST、MSI、MSIC、PLESSEY、ITF14、EAN14 PDF417、QR CODE、Data Matrix		
Print head position sensor	Micro switch		
Media type	Label, Sticker, Continuous, gap, black mark, fan-fold and punched hole		
Paper off type	Tear off & peel off		
Internal font	FONT 0 to FONT 8; Commonly used in single-byte fonts		
Enlargement & rotation	1to10 times enlargement in both directions; 0°, 90°, 180°, 270°, 360° rotation		
Gross weight	1.50 kg		
Dimension	231(D) x 163(W) x 150.7(H)mm		
Work enviroment	5~45°C, 20~80%RH		
Storage enviroment	-40~55°C, ≤93%RH(40°C)		
Drivers	Win XP/Win 7/Win 8/Win 10/Android/IOS		
Input	24VDC, 2.5A		
Paper exists detection	Photoelectric sensor		
Interface	USB+Serial	USB+Bluetooth	Serial+USB+Lan
Memory	DRAM: 4M; FLASH: 4M		
Image	Monochromatic PCX, BMP image files can be load to FLASH, DRAM		



Scan QR code to checkout Xprinter website for more update information.  
Phone: (+86 756) 3895 852  
[Http://www.poskeytech.com](http://www.poskeytech.com)  
Email: [overseas@xprinter.net](mailto:overseas@xprinter.net)

