

## XP-T58L

### Direct thermal Printer

- Big gear printing head
- Outstanding functions, Strong stability
- Support main stream OS systems
- Support simplified/traditional Chinese, Japanese, Korean and many other international Languages
- Support Chinese GB18030
- Avoid order missing
- Support OPOS driver



Restaurant



Shopping





Mart



Interface

# XP-T58L

## Direct thermal Printer



<b>Model</b>	<b>XP-T58L</b>
Printing method	Direct thermal
Paper width	57.5±0.5mm
Print width	48 mm
Column capacity	384 dots/line
Printing speed	90mm/s Max.
Interface	USB / Parallel
Line spacing	3.75mm (Adjustable by commands)
<b>Fonts Symbology</b>	
Character size	Afont A: 12x24, Font B: 9x17, CHN: 24*24
Characters /Line	Font A: 32 chars Font B: 42 chars CHN: 16 Character Sets
1D Barcode	UPC-A / UPC-E / JAN13(EAN13) / JAN8(EAN8) / CODE39 / ITF / CODABAR / CODE93 / CODE128
Input buffer	32 Kbytes
NV Flash	64 Kbytes
<b>Power</b>	
Power adaptor	Input: AC 110V/220V, 50 ~ 60Hz Output: DC 12V/2.6A
Power source	DC 12V/2.6A
Cash drawer	DC 12V/1A
<b>Physical characteristics</b>	
Weight	0.68 kg
Dimensions	170 x 125 x 119.5mm (D×W×H)
<b>Environmental Requirements</b>	
Work environment	Temperature (0 ~ 45°C) humidity(10 ~ 80%)
Storage environment	Temperature(-10 ~ 60°C) humidity(10 ~ 80%)
<b>Reliability</b>	
Printer head life	50 KM
<b>Software</b>	
Emulation	ESC/POS
Driver	Windows/Linux/Android/Mac
Utility	Windows & Linux test Utility
SDK	iOS/ Android/ Windows



Scan QR code to checkout Xprinter website for more update information.  
 Phone: (+86 756) 3895 852  
[Http://www.xprintertech.com](http://www.xprintertech.com)  
 Email: [overseas@xprinter.net](mailto:overseas@xprinter.net)

